

# Be-dunkel

## SBK-08 Shotcrete powder - dark

### SBK-08 Shotcrete and putty powder

#### Specifications

- ❶ Dark (dark grey) shotcrete powder for the reconstruction of the exposed concrete surface.
- ❷ Can be mixed with structure putty powder SSP and SBK-08 colour pigments.
- ❸ Use only together with SBK-08 Rep-hell and structure putty powder SSP and only with the tested permanent impregnation Neutec LT 342, LT 344 und LT 425.

#### Storage:

Store dry, Keep the container always tightly closed.

**Storage life:** 12 months from delivery date until use

**Disposal:** The product must not enter effluent or sewerage. Please comply with the applicable regulations for the proper disposal of waste on federal, cantonal and communal levels.

#### Instruction of use / processing

##### Primer (adhesive surface):

The substrate must be clean and free from dust, fat and oil.

**Be-dunkel** establishes a firm connection of upper and base material. Prime the base 2 times with pure **M-10** (mixed water) for highly absorbent substrates.

##### Mixing rate for spraying process:

Mix 1 part **Be-dunkel** well with 1 part **M-10** (mixed water) and repot and sieve it before use.

##### Mixing rate for structure putty application:

Mix approx. 3 parts **Be-dunkel** well with 1 part **M-10** (mixed water).

##### Processing temperature:

8° – 40°C, protect unprocessed material from humidity.

##### Cleaning of tools / disposal:

The cleaning shall be conducted with tap water. The product must not enter effluent or sewerage. Mixed rests have to dry in the bucket and are disposed then.

## Technical data:

<b>Form</b>	Powder "Contains Portland cement"
<b>Colour:</b>	dark grey
<b>Packaging / delivery form:</b>	15 kg oval bucket
<b>Storage suitability</b>	Keep the container always tightly closed and dry.
<b>Transportation regulations</b>	Non-dangerous goods in terms of transportation.

## Hazard warnings

### "Contains Portland cement"

H315 Causes skin irritation.  
 H318 Causes severe eye damages.  
 H335 May cause respiratory irritation.  
 P261 Avoid inhalation of dust.  
 P280 Wear protective gloves / eye protection.  
 P305+P351+P338 IN CASE OF CONTACT WITH EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately give call to the POISON CONTROL CENTRE or medical doctor.  
 P304+P340 IF INHALED: Move the affected person to fresh air and ensure unhindered breathing.  
 P403+P233 Store in a well-ventilated place. Keep the container always tightly closed.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.



The information provided here represents our best knowledge and experience to date. However, it implies no liability. Changes in terms of technical progress and operational development remain reserved. All information simply defines the specification of our products and services and imply no guarantee. The performance of the products described herein should be verified by testing and carrying out the functions. The testing of product suitability is in the clear responsibility of the customer and has to be conducted by authorised personnel. This also applies to the trade mark rights of third parties.

**Version: January 2016**

This document is superseded when a new edition appears.